

PRO-HYDRO-TOOLS



HHY - 120A / HHY - 300A



HHY - 70A



HHY - 430
(HANDLE VALVES)



HHY - 400A



HHY - 300C / HHY - 400



HHYJ - 80
MECHANICAL



HHY - 400E
(LIGHTWEIGHT)



HHY - 150



HYDRAULIC CRIMPING TOOLS

MODEL	MAX PRESSURE (Ton)	MAX STROKE (mm)	CRIMP RANGE (mm)	SIZE OF STANDARD DIES (mm)	CRIMP PATTERN	WEIGHT (Kg)
HHY-70A	8	12	6-70	6,10, 16, 25, 35, 50, 70	HEXAGONAL TYPE	2.6
HHY-120A	10	14	10-120	10,16, 25, 35, 50, 70, 95, 120	HEXAGONAL TYPE	5
HHY-300A	13	18	16-300	16, 25, 35, 50, 70, 95, 120, 150, 185, 240, 300	HEXAGONAL TYPE	7
HHY-400A	16	24	16-400	16, 25, 35, 50, 70, 95, 120, 150, 185, 240, 300, 400	HEXAGONAL TYPE	13.5
HHY-300C	14	30	16-300	16, 25, 35, 50, 70, 95, 120, 150, 185, 240, 300	HEXAGONAL TYPE	11
HHY-400	12	32	16-400	16, 25, 35, 50, 70, 95, 120, 150, 185, 240, 300, 400	HEXAGONAL TYPE	10.5
HHY-400E	12	42	16-400	16, 25, 35, 50, 70, 95, 120, 150, 185, 240, 300, 400	HEXAGONAL TYPE	4.8
HHY-430	11	32	16-400	16, 25, 35, 50, 70, 95, 120, 150, 185, 240, 300, 400	HEXAGONAL TYPE	11
HHY-150	12	18	16-150	Male : 8-38, 60-150 / Female : 14-22, 38-60, 70-80, 100-150	RADIAN TYPE	8.2
HHYJ-80	-	-	8-80	MECHANICAL CRIMPING TOOLS	HEXAGONAL TYPE	3

BATTERY POWERED CRIMPING
HHYZ - 400



HHY - 100TF



HHY - 1000F
/ HHY - 630F



HHY - 430F



HHY - 500F



HHY 300CF



MULTI-FUNCTIONAL : HHY-60HF
CRIMPING-CUTTING-PUNCHING



SEPARABLE HYDRAULIC CRIMPING TOOLS

MODEL	MAX PRESSURE (Ton)	MAX STROKE (mm)	CRIMP RANGE (mm)	SIZE OF STANDARD DIES (mm)	CRIMP PATTERN	WEIGHT (Kg)
HHY-300CF	14	30	16-300	16, 25, 35, 50, 70, 95, 120, 150, 185, 240, 300	HEXAGONAL TYPE	4.8
HHY-430F	16	25	16-400	16, 25, 35, 50, 70, 95, 120, 150, 185, 240, 300, 400	HEXAGONAL TYPE	6.5
HHY-500F	20	22	16-500	16, 25, 35, 50, 70, 95, 120, 150, 185, 240, 300, 400, 500	HEXAGONAL TYPE	7.2
HHY-630F	25	22	150-630	240, 300, 400, 500, 600	HEXAGONAL TYPE	13.5
HHY-1000F	35	30	240-1000	400, 500, 630, 800, 1000	HEXAGONAL TYPE	24
HHY-100TF	100	24	Sub sleeve pipe of aluminium end of copper 76mm/ steel sleeve pipe 36 mm		HEXAGONAL TYPE	43.5
HHY-200TF	200	40	300-1440	630, 800, 1000, 1140, 1440	HEXAGONAL TYPE	110

HHY - 200TF





HHD - 30J



HHD - 500



HHD - 85F
HHD - 120F



HHD - 40



HHD - 30



HHD - 50F



HHD - 40F



HHD - 85

HYDRAULIC CABLE CUTTERS

MODEL	MAX PRESSURE (Ton)	MAX CUTTING RANGE (mm)			WEIGHT (Kg)
		TELEPHONE CABLE	LEAD SHEATHED CABLE (XLPE)	UNDERGROUND CABLE	
HHD - 30	7	30	30	30	6
HHD - 40	7	40	40	40	6
HHD - 85	5	85	85	85	15
HHD - 40F	5	40	40	40	3.8
HHD - 50F	12	50	50	50	8
HHD - 85F	5	85	85	50	10
HHD - 120F	8	120	120	75	13
HHD - 30J	CUT 620 mm ² ACSR AND 100 mm ² STEEL WIRE ROPES				3.6
HHD - 500	CUT 400 mm ² COPPER AND ALUMINUM WIRE				3



HHDK - 8



HHK - 8D / HHK - 15



HHK - 8A



PUNCHES DIES (OPTION)

HYDRAULIC HOLE DIGGERS

MODEL	MAX PRESSURE (Ton)	MAX STROKE (mm)	PUNCH DIES	MAX. THICKNESS (mm)		WEIGHT (Kg)
				STAINLESS	IRON	
HHK - 8	5	20	φ 26 φ 35	1	2	17.5
HHK - 8A	11	20	φ 22 φ 27 φ 34 φ 43 φ 49 φ 60	1.6	3.2	8
HHK - 8D	11	22	φ 22 φ 27 φ 34 φ 43 φ 49 φ 60	1.6	3.2	12.5
HHK - 15	13	22	φ 63 φ 76 φ 80 φ 89 φ 100 φ 114	2	4	27

*option size φ 16,20,26,32,39,51



HHBX - 40



HHBX - 30

CABLE STRIPPERS

MODEL	STRIPPING INSULATED (mm)
HHBX-30	8-16
HHBX-40	14-40



HHJX - 20



HHP - 2

WIRE ROPE PULLING HOIST 2 TON

MODEL	STEEL WIRWE ROPES , ACSR (mm)
HHP-2	DIAMETER 6.0mm / LENGTHY 2200mm
HHJX-20	DIAMETER 7.0mm / LENGTHY 1500mm

WIRE PULLING GRIPS

MODEL	STEEL WIRE ROPES , ACSR (mm)
HHKX-1	2.5-16
HHKX-2	4-22
HHKX-3	16-32



HHKX - 3

WIRE PULLING GRIPS

MODEL	CU-AL CABLE (mm ²)
HHKX-1L	25-70
HHKX-2L	95-120
HHKX-3L	150-240



HHKX - 1L