



HHL-5-S

HYDRAULIC EASY PULLER

MODEL	MAX PRESSURE (Ton)	STROKE (mm)	SPREAD (mm)	REACH (mm)	WEIGHT (Kg)
HHL-5 S	5	50	250	163	10
HHL-10 S	10	60	300	200	12
HHL-20 S	20	70	400	238	19



HHL-5F



HHL-5

MODEL	MAX PRESSURE (Ton)	STROKE (mm)	SPREAD (mm)	REACH (mm)	WEIGHT (Kg)
HHL-5	5	50	200	140	7.5
HHL-10	10	50	250	170	11
HHL-20	20	60	350	205	19
HHL-30	30	60	400	220	25
HHL-50	50	60	500	250	43
HHL-5F	5	50	200	140	15
HHL-10F	10	50	250	170	20
HHL-20F	20	60	350	205	27
HHL-30F	30	60	400	220	35
HHL-50F	50	60	500	250	55



FITTING TOOLS KIT

MODEL	UMH-36
IMPACT	36
COLLET BORE(mm)	10-55
COLLET od(mm)	26-120



HHQ-1319

HYDRAULIC NUT SPLITTERS

MODEL	MAX PRESSURE (Ton)	SPLITTING RANGE (mm)	WEIGHT (Kg)
HHQ-1319	5	M6-M12	1.5
HHQ-1924	10	M12-M16	2
HHQ-2432	15	M16-M22	3.5
HHQ-3241	20	M22-M27	4.5
HHQ-4150	35	M27-M33	8.2
HHQ-5060	50	M33-M39	11.8
HHQ-6070	90	M39-M48	34.1



K3-SERIES



K22-SERIES

MODEL	SPREAD (mm)
K3-50	12-70
K3-100	26-139
K3-160	50-205
K3-260	90-335
K3-380	140-457

MODEL	SPREAD (mm)
K22-50	30-50
K22-75	50-75
K22-105	75-105
K22-150	80-150



UMH-100



UMH-200N

STANDARD YOKE	MIN BORE
10X10X150	15mm
14X14X150	20mm
20X20X150	30mm
30X30X150	45mm
40X40X150	60mm

STANDARD YOKE	MIN BORE
14X14X250	20mm
20X20X250	30mm
30X30X250	45mm
45X45X250	65mm

BEARING HEATER

MODEL	UMH-100	UMH-200
VOLTAGE	230 V / 10A	230 V / 16A
POWER RATING	2.5KVA	3.6KVA
FREQUENCY	50/60 Hz	50/60 Hz
MAX.TEMPERATURE(APPROX)	150 C	240 C
FIGURE DIMENSION	240*200*235mm	508*370*340mm
MIN BORE DIAMETER OF WORK PIECE(VERTICA/HORIZONTAL)	15mm / 60mm	20mm / 65mm
MAX.O.D.OF WORK PIECE	220 mm	480 mm
MIN. WIDTH OF WORK PIECE (VERTICA/HORIZONTAL)	65mm / 95mm	130mm / 195mm

HHP-1054



HHP-538

HYDRAULIC FLANGE SPREADER

MODEL	MAX PRESSURE (Ton)	TIP CLEARANCE (mm)	STROKE (mm)	THICKNESS (mm)	STUD SIZE (Kg)
HHP-538	5	38	2X57	19X28	6
HHP-1054	10	54	2X92	31X41	13.5



HHP-1481



HHP-10

HYDRAULIC FLANGE SPREADER

MODEL	MAX PRESSURE (Ton)	TIP CLEARANCE (mm)	SPREAD (mm)	WEIGHT (Kg)
HHP-1481	14	6.1	81	9
HHP-10	10	6.1	81	11.5